











AD16-16 Buzzer Round, Square, Rectangle

Name	Type	Model	Color	Lamp Voltage	Appearance dimension
Indicators (plug-in type wiring)		AD16-16D/□■	red-r green-g yellow-y white-w blue-b	21-AC.DC 6V 22-AC.DC 12V 23-AC.DC 24V 24-AC.DC 36V 25-AC.DC 48V 26-AC.DC 110V 27-AC.DC 127V 28-AC.DC 220V 31-AC 220V 32-AC 380V	
Indicators (screw type wiring)		AD16-16DL/□■			

Description:

□ in the column of model is indicated with color, ■ is indicated with voltage class code.

Name	Type	Model	Lamp Voltage	Calling Method	Rated Sound Pressure and Frequency	Appearance dimension
Buzzers (Round)		AD16-16M/□■				
Buzzers (Square)		AD16-16MF/□■	21-AC.DC 6V 22-AC.DC 12V 23-AC.DC 24V 24-AC.DC 36V 25-AC.DC 48V	A (intermittent) B (whistling)	75dB (10cm) (under rated voltage) 2300Hz±400Hz	Wiring terminal 2.8x0.5 Thickness of mounting plate 1-6 Square top view Round top view 
Buzzers (Rectangular)		AD16-16MJ/□■				Rectangular top view 

Description:

“□” in the column of model is indicated with the letter of calling method, “■” is indicated with voltage class code.